





CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



TERM. NO.'s FOR REF. ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-1 @20°C	0.088 ohms max.
D.C. RESISTANCE	3-4 @20°C	0.057 ohms max.
D.C. RESISTANCE	5-7 tie(5+6, 7+8), @20°C	0.011 ohms max.
INDUCTANCE	3-4 10kHz, 100mVAC, Ls	25.00uH ±10%
SATURATION CURRENT	20% rolloff from initial	2.5A
LEAKAGE INDUCTANCE	3-4 tie(1+2, 5+6+7+8), 100kHz, 10mVAC, Ls	130nH typ., 250nH max.
DIELECTRIC	tie(2+3, 5+6), 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(3-4):(2-1)	3:1, ±1%
URNS RATIO	(3-4):(5+6-7+8)	3:1, ±1%

REV.	DATE	Packaging Specifications
		Method: Tape & Reel
		PKG-0328
6A	6/10	



CONVENTION PLACEMENT

Tolerances unless otherwise specified:
Angles: ±1° Decimals: ±.005 [.13]
Fractions: ±1/64 Footprint: ±.005 [.13]
This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER

eiSos p/n: **FKS750311675**



PART NO.
FKS750311675

SPECIFICATION SHEET 1 OF 1