


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	7-5	tie(5+6, 7+8), @20°C
D.C. RESISTANCE	1-4	tie(1+2, 3+4), @20°C
INDUCTANCE	7-5	tie(5+6, 7+8), 100kHz, 100mVAC, Ls
SATURATION CURRENT	7-5	tie(5+6, 7+8), 20% rolloff from initial
LEAKAGE INDUCTANCE	7-5	tie(5+6, 7+8, 1+2+3+4), 100kHz, 10mVAC, Ls
DIELECTRIC	8-1	tie(5+6, 3+4), 1875VAC, 1 second
URNS RATIO	(7-5):(1-4), tie(5+6, 7+8, 1+2, 3+4)	1:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:
-Functional insulation only.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications	 CONVENTION PLACEMENT	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
		Method: Tape & Reel PKG-0328		Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	TRANSFORMER	FKS750317253
6A	5/18			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750317253	SPECIFICATION SHEET 1 OF 1

