




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



Customer to tie terminals 2&3 on PC board.

Application of the transformer allows for the leadwires between terminals 2&3 to solder bridge.



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-4 tie(2+3), @20°C	0.190 ohms ±10%
D.C. RESISTANCE	7-8 @20°C	0.325 ohms ±10%
D.C. RESISTANCE	8-9 @20°C	0.200 ohms ±10%
D.C. RESISTANCE	10-11 @20°C	0.350 ohms ±10%
D.C. RESISTANCE	11-12 @20°C	0.215 ohms ±10%
INDUCTANCE	1-4 tie(2+3), 10kHz, 100mVAC, Ls	68.0uH ±10%
SATURATION CURRENT	20% rolloff from initial	1.8A
LEAKAGE INDUCTANCE	1-4 tie(2+3, 7+9, 10+12), 100kHz, 100mVAC, Ls	0.6uH typ., 1.2uH max.
DIELECTRIC	1-12 tie(2+3, 9+10), 4000VAC, 1 second	4000VAC, 1 minute
DIELECTRIC	7-12 625VAC, 1 second	-
URNS RATIO	(2-4):(1-3)	1:1, ±1%
URNS RATIO	(1-4):(7-8), tie(2+3)	1.1:1, ±1%
URNS RATIO	(1-4):(8-9), tie(2+3)	1.833:1, ±1%
URNS RATIO	(1-4):(10-11), tie(2+3)	1.1:1, ±1%
URNS RATIO	(1-4):(11-12), tie(2+3)	1.833:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:

- Reinforced insulation for a primary circuit at a working voltage of 400VDC.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	CONVENTION PLACEMENT	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
		Method: Tape & Reel PKG-0799		Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	TRANSFORMER	FKS750314851
6A	3/15			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750314851	SPECIFICATION SHEET 1 OF 1

