




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



* DIMENSION MAY BE EXCEEDED WITH SOLDER ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	0.200 ohms max.
D.C. RESISTANCE	8-7 @20°C	0.060 ohms max.
INDUCTANCE	8-7 50kHz, 100mVAC, Ls	20uH ±10%
SATURATION CURRENT	20% rolloff from initial	2A
LEAKAGE INDUCTANCE	8-7 tie(1+3), 100kHz, 100mVAC, Ls	0.270uH max.
DIELECTRIC	1-8 4500VAC, 1 second	4500VAC, 1 minute
URNS RATIO	(1-3):(8-7)	2.4:1, ±2%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Wire insulation & RoHS status not affected by wire color.
 Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	CONVENTION PLACEMENT	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.001 [.03]	DRAWING TITLE	PART NO.
		Method: Tray PKG-0735			TRANSFORMER	FKS750342627
6A	8/15			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750342627	SPECIFICATION SHEET 1 OF 1

