


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



#### ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:



PARAMETER	TEST CONDITIONS	VALUE
6B D.C. RESISTANCE	5-8 @20°C	0.150 ohms ±15%
D.C. RESISTANCE	1-4 @20°C	0.197 ohms ±10%
INDUCTANCE	5-8 10kHz, 100mVAC, Ls	26.00uH ±10%
SATURATION CURRENT	5-8 20% rolloff from initial	960mA
6B LEAKAGE INDUCTANCE	5-8 tie(1+4), 100kHz, 100mVAC, Ls	390nH typ., 650nH max.
6B DIELECTRIC	1-8 1875VAC, 2 seconds	1500VAC, 1 minute
URNS RATIO	(1-4):(5-8)	1.09:1, ±1%

#### GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC61010-1 and IEC61131-2:

- Minimum creepage distance of 1.6mm for Basic insulation.



Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-1042	CONVENTION PLACEMENT	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. FKS750315246
6B	7/17			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750315246	SPECIFICATION SHEET 1 OF 1
6A	10/15					

