



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Au100%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	3-4 @20°C	3.0 mOhms max.
D.C. RESISTANCE	4-5 @20°C	3.0 mOhms max.
D.C. RESISTANCE	7-11 @20°C	3.5 mOhms max.
INDUCTANCE	3-5 100kHz, 100mVAC, Ls	145.0uH min.
LEAKAGE INDUCTANCE	3-5 tie(7+11), 100kHz, 100mVAC, Ls	250nH max.
DIELECTRIC	3-7 2250VDC, 1 second	-
URNS RATIO	(7-11):(3-4)	1.333:1, ±1%
URNS RATIO	(7-11):(4-5)	1.333:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

REV.	DATE	Packaging Specifications	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
6E	5/14	Method: Tape & Reel	Angles: ±1°	TRANSFORMER	FKS750341135
6D	4/13	PKG-0793	Decimals: ±.005 [.13]		
6C	11/12		Fractions: ±1/64		
6B	4/12		Footprint: ±.005 [.13]		
			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750341135	SPECIFICATION SHEET 1 OF 1

