




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-4 @20°C	0.805 ohms ±10%
D.C. RESISTANCE	11-12 @20°C	0.28 mOhms max.
INDUCTANCE	2-4 10kHz, 100mVAC, Ls	5.60mH min.
DIELECTRIC	2-12 1500VAC, 2 seconds	-
URNS RATIO	(2-4):(11-12)	100:1, ±1%

6B



GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Voltage-time product: 248 Vusec min. on SEC based on unipolar waveform.

Recommended burden resistor: 100 Ohms

Current Rating: 40A on PRI

6C UL recognized class B insulation system M1-130(B), E106391.
- Core is not considered to be dead metal.

6C Functional insulation only.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
6D	9/19	Method: Tape & Reel	Angles: ±1°	TRANSFORMER	FKS750316794
6C	8/18	PKG-1139	Fractions: ±1/64		
6B	1/18		Decimals: ±.005 [.13]		
6A	9/17		Footprint: ±.005 [.13]		
			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: FKS750316794	SPECIFICATION SHEET 1 OF 1

