



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes




TERM. NO.'s FOR REF. ONLY



LOT CODE & DATE CODE

6B



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-4 @20°C	2.630 ohms ±10%
D.C. RESISTANCE	11-12 @20°C	0.28 mOhms max.
INDUCTANCE	2-4 10kHz, 100mVAC, Ls	22.40mH min.
DIELECTRIC	2-12 1500VAC, 2 seconds	-
URNS RATIO	(2-4):(11-12)	200:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Voltage-time product: 496 Vusec min. on SEC based on unipolar waveform.

Recommended burden resistor: 200 Ohms

Current Rating: 40A on PRI

6C UL recognized class B insulation system M1-130(B), E106391.
- Core is not considered to be dead metal.

6C Functional insulation only.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications
6D	9/19	Method: Tape & Reel
6C	8/18	PKG-1139
6B	1/18	
6A	9/17	



CONVENTION PLACEMENT

Tolerances unless otherwise specified:
Angles: ±1°
Fractions: ±1/64
Decimals: ±.005 [.13]
Footprint: ±.005 [.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE

TRANSFORMER

eiSos p/n: FKS750316796



PART NO.

FKS750316796

SPECIFICATION SHEET 1 OF 1